



AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A polymer compound characterized by comprising a monomer unit represented by formula (1)-(2):




wherein, ~~A represents a triphenyl boron group in which the phenyl group may be substituted,~~ R^{16} represents a hydrogen atom or an alkyl group having 1 to 12 carbon atoms, ~~X atoms;~~ X represents a single bond, -O-, -S-, -SO-, -SO₂- or a divalent hydrocarbon group having 1 to 20 carbon atoms which may have a hetero atom; and R^1 to R^{15} independently represent a hydrogen atom, a halogen atom, a cyano group, an amino group, a hydrocarbon alkyl group having 1 to 12 carbon atoms, an alkoxy group having 1 to 12 carbon atoms, an aryloxy group, an

aromatic group or a heterocyclic group; and wherein among R¹ to R¹⁵, those adjacent to each other on one phenyl group may be bonded to form a condensed ring.

2. (canceled).


3. (currently amended): The polymer compound as claimed in ~~claim 2~~claim 1, wherein in the monomer unit represented by formula (2), at least four of R¹, R⁴, R⁵, R⁹, R¹⁰ and R¹³ each represent an alkyl group having 1 to 6 carbon atoms or alkoxy group having 1 to 6 carbon atoms (provided that R¹ and R⁴ are at ortho positions with respect to the substitution position of the boron atom).

4. (currently amended): The polymer compound as claimed in ~~claim 2~~claim 1, comprising a monomer unit represented by formula (3):



wherein, R², R³, R⁶ to R⁸, R¹¹, R¹², R¹⁵ and R¹⁶ represent the same meanings as defined in ~~above~~
formula (2).

5. (currently amended): The polymer compound as claimed in ~~claim 2~~claim 1, comprising a monomer unit represented by formula (4):



wherein R^1 to R^6 , R^8 to R^{13} and R^{16} have the same meanings as defined in ~~above 2~~formula (2) respectively, R^{17} to R^{26} independently represent a hydrogen atom, a halogen atom, a cyano group, an amino group, a hydrocarbon alkyl group having 1 to 12 carbon atoms, an alkoxy group having 1 to 12 carbon atoms, an aryloxy group, an aromatic group or a heterocyclic group. ~~Amonggroup, and wherein among~~ R^{17} to R^{26} , those adjacent to each other on one phenyl group may be bonded with each other to form a condensed ring.

6. (currently amended): The polymer compound as claimed in ~~claim 2~~claim 1, which is a light-emitting polymer compound comprising the monomer unit represented by ~~formula (2)~~ formula (2) described in ~~claim 2~~claim 1 and a light-emitting monomer unit.

7. (original): The light-emitting polymer compound as claimed in claim 6, wherein light emitted by the light-emitting monomer unit is phosphorescence.

8. (original): The light-emitting polymer compound as claimed in claim 7, wherein the light-emitting monomer contains a transition metal complex.

9. (original): The light-emitting polymer compound as claimed in claim 8, wherein the light-emitting monomer unit contains a metal selected from metals of atomic numbers 39 to 48 and 72 to 80.

10. (currently amended): The light-emitting polymer compound as claimed in ~~claim 2~~claim 1, wherein the light-emitting polymer compound contains a hole-transporting monomer unit.

11. (currently amended): A light-emitting composition, comprising a polymer compound containing the monomer unit represented by formula (2) described in ~~claim 2~~claim 1 and a light-emitting compound.

12. (original): The light-emitting composition as claimed in claim 11, wherein the light-emitting compound is a low molecular weight compound or a polymer compound.

13. (previously presented): An organic light-emitting device comprising one or more polymer layers between an anode and a cathode, wherein at least one of the polymer layers present between the anode and the cathode comprises the light-emitting polymer compound described in claim 6.

14. (currently amended): An organic light-emitting device comprising one or more polymer layers between an anode and a cathode, wherein at least one of the polymer layers present between the anode and the cathode ~~comprises the~~comprises the light-emitting composition described in claim 11.

15. (currently amended): A light source for surface emission, a backlight for a display unit, a display unit, an illumination device or an interior or exterior accessory ~~using the light-emitting device described in claim 13~~ comprising the light emitting device described in claim 13.